



7 – INDUSTRIAL FIXTURES

Industrial lighting fixtures for intensive use and demand. Yphix LED High bays, LED Tri-Proof and LED Tube fixtures are great for industrial spaces like warehouses, production facilities, spaces with very tall ceilings, workspaces and garages. Available with a transparent or milky white cap. All industrial fixtures are vandalism-proof and up to IP65 waterproof. All Yphix Industrial fixtures are connectable, which minimizes labour time during installation.

YPHIX INDUSTRIAL FIXTURES QUALITY FEATURES:







- IK08 vandalism-proof
- Up to IP65 waterproof
- Quick and easy assembly
- High bay CCT: 4000K or 6500K
- High bay motion sensor optional

Aquaproof



50504170

Pro line






SKU	Product name	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dim-mable	Lifetime (hrs)	Wattage (W)	Input Voltage	Lumen (Lm)	Kelvin value (K)	CRI	IK Value	Beam angle	Connectable
 50504170	LED TL fixture Aquaproof Pro Line 1 x 60cm IP65	668	62	58	IP65	Light grey				220-240V AC				IK08		No
 50504171	LED TL fixture Aquaproof Pro Line 2 x 60cm IP65	668	100	58	IP65	Light grey				220-240V AC				IK08		No
 50504172	LED TL fixture Aquaproof Pro Line 1 x 120cm IP65	1272	62	58	IP65	Light grey				220-240V AC				IK08		No
 50504173	LED TL fixture Aquaproof Pro Line 2 x 120cm IP65	1272	100	58	IP65	Light grey				220-240V AC				IK08		No
 50504174	LED TL fixture Aquaproof Pro Line 1 x 150cm IP65	1572	62	58	IP65	Light grey				220-240V AC				IK08		No
 50504175	LED TL fixture Aquaproof Pro Line 2 x 150cm IP65	1572	100	58	IP65	Light grey				220-240V AC				IK08		No

Aquaproof





50504150

Premium line

SKU	Product name	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dim-mable	Lifetime (hrs)	Wattage (W)	Input Voltage	Lumen (Lm)	Kelvin value (K)	CRI	IK Value	Beam angle	Connectable
 50504150	LED Tri-proof fixture Aquaproof Premium Line 60cm 18W 4000K IP65 connectable	600	70	65	IP65	Light grey	No	35000	18	220-240V AC	2730	4000K	>80	IK08	150°	Yes
 50504151	LED Tri-proof fixture Aquaproof Premium Line 120cm 36W 4000K IP65 connectable	1200	70	65	IP65	Light grey	No	35000	36	220-240V AC	5200	4000K	>80	IK08	150°	Yes
 50504152	LED Tri-proof fixture Aquaproof Premium Line 150cm 45W 4000K IP65 connectable	1500	70	65	IP65	Light grey	No	35000	45	220-240V AC	6650	4000K	>80	IK08	150°	Yes
 50504153	LED Tri-proof fixture Aquaproof Premium Line sensor 120cm 36W 4000K IP65 connectable	1200	70	65	IP65	Light grey	No	35000	36	220-240V AC	5200	4000K	>80	IK08	150°	Yes
 50504154	LED Tri-proof fixture Aquaproof Premium Line sensor 150cm 46W 4000K IP65 connectable	1500	70	65	IP65	Light grey	No	35000	46	220-240V AC	6650	4000K	>80	IK08	150°	Yes



SKU	Product name	Diameter (mm)	Height (mm)	IP value	Colour	Dim-mable	Lifetime (hrs)	Wattage (W)	Input Voltage	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
	50230710 LED High bay Premium Line 100W 4000K IP65	Ø286	110	IP65	Black	Yes	54000	100	220-240V AC	16000	4000	>80	120°
	50230715 LED High bay Premium Line 150W 4000K IP65	Ø286	110	IP65	Black	Yes	54000	150	220-240V AC	24000	4000	>80	120°
	50230720 LED High bay Premium Line 200W 4000K IP65	Ø340	110	IP65	Black	Yes	54000	200	220-240V AC	32000	4000	>80	120°
	50230711 LED High bay Premium Line 100W 6000K IP65	Ø286	110	IP65	Black	Yes	54000	100	220-240V AC	16000	6000	>80	120°
	50230716 LED High bay Premium Line 150W 6000K IP65	Ø286	110	IP65	Black	Yes	54000	150	220-240V AC	24000	6000	>80	120°
	50230721 LED High bay Premium Line 200W 6000K IP65	Ø340	110	IP65	Black	Yes	54000	200	220-240V AC	32000	6000	>80	120°



SKU	Product name	Diameter (mm)	Height (mm)	IP value	Colour	Installation height (mm)	Mounting height (m)	Detection range (m)	Dimming control output (v)	Time setting
	50230800 Motion sensor for LED High bay	Ø55	19,8	IP65	White	41,3	max 12	max 12	0-10	10 sec/1 min/5 min/10 min/.../60 min

