




3 - LED DOWNLIGHTS (LED INCLUDED)

Versatile range of LED Downlights and Spots for many applications, LED included. Waterproof (IP65) or higher, which makes them perfect for outdoor spaces and moist indoor areas, like bathrooms and swimming pools. They all work with a small-sized driver and are perfectly dimmable. Available in 9mm, the smallest built-in height in the market. Also available in a unique design without an outside aluminium or Stainless Steel spring ring with only the light source visible.


YPHIX DOWNLIGHT AND SPOTS QUALITY FEATURES:

- Water resistance (IP44, IP65 or IP66)
- Dimmable in all Yphix options (wall dimmer, Zigbee, RF)
- Smallest built-in height (11mm) available in the market
- Available in black, white and aluminium colours
- Square and round designs
- All LED downlights have a unique design without spring ring
- Most are tiltable
- Guarantee: 3 years






LED downlight Pro Line

SKU	Product name	Diameter (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Input Voltage	Installation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
50416308	LED downlight Pro Line white 7W 3000K	Ø100	32	IP20	White (RAL 9003)	No	30000	7	220-240V AC	32	Ø70	500	3000K	>80	120°
50416314	LED downlight Pro Line white 13W 3000K	Ø145	32	IP20	White (RAL 9003)	No	30000	13	220-240V AC	32	Ø110	1200	3000K	>80	120°
50416320	LED downlight Pro Line white 20W 3000K	Ø170	32	IP20	White (RAL 9003)	No	30000	20	220-240V AC	32	Ø135	2000	3000K	>80	120°
50416328	LED downlight Pro Line white 26W 3000K	Ø230	32	IP20	White (RAL 9003)	No	30000	26	220-240V AC	32	Ø190	3000	3000K	>80	120°
50418408	LED downlight Pro Line white 7W 4000K	Ø100	32	IP20	White (RAL 9003)	No	30000	7	220-240V AC	32	Ø70	550	4000K	>80	120°
50418414	LED downlight Pro Line white 13W 4000K	Ø145	32	IP20	White (RAL 9003)	No	30000	13	220-240V AC	32	Ø110	1300	4000K	>80	120°
50418420	LED downlight Pro Line white 20W 4000K	Ø170	32	IP20	White (RAL 9003)	No	30000	20	220-240V AC	32	Ø135	2100	4000K	>80	120°
50418428	LED downlight Pro Line white 26W 4000K	Ø230	32	IP20	White (RAL 9003)	No	30000	26	220-240V AC	32	Ø190	3200	4000K	>80	120°



LED downlight Premium Line

SKU	Product name	Diameter (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Input Voltage	Installation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
50413008	LED downlight Premium Line white 9W 3000K IP44 dimmable	Ø117	22	IP44	White (RAL 9003)	Yes	30000	9	220-240V AC	25	Ø110	530	3000K	>80	120°
50413011	LED downlight Premium Line white 11W 3000K IP44 dimmable	Ø180	22	IP44	White (RAL 9003)	Yes	30000	11	220-240V AC	25	Ø165	820	3000K	>80	120°
50413015	LED downlight Premium Line white 15W 3000K IP44 dimmable	Ø240	22	IP44	White (RAL 9003)	Yes	30000	15	220-240V AC	25	Ø225	1150	3000K	>80	120°
50413108	LED downlight Premium Line white 9W 4000K IP44 dimmable	Ø117	22	IP44	White (RAL 9003)	Yes	30000	9	220-240V AC	25	Ø110	530	4000K	>80	120°
50413111	LED downlight Premium Line white 11W 4000K IP44 dimmable	Ø180	22	IP44	White (RAL 9003)	Yes	30000	11	220-240V AC	25	Ø165	820	4000K	>80	120°
50413114	LED downlight Premium Line white 15W 4000K IP44 dimmable	Ø240	22	IP44	White (RAL 9003)	Yes	30000	15	220-240V AC	25	Ø225	1150	4000K	>80	120°
50415308	LED downlight Premium Line black 9W 3000K IP44 dimmable	Ø117	22	IP44	Black (RAL 9005)	Yes	30000	9	220-240V AC	25	Ø110	520	3000K	>80	120°
50415311	LED downlight Premium Line black 11W 3000K IP44 dimmable	Ø180	22	IP44	Black (RAL 9005)	Yes	30000	11	220-240V AC	25	Ø165	750	3000K	>80	120°
50415315	LED downlight Premium Line black 15W 3000K IP44 dimmable	Ø240	22	IP44	Black (RAL 9005)	Yes	30000	15	220-240V AC	25	Ø225	1000	3000K	>80	120°




SKU	Product name	Diameter (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Input Voltage	Installation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
 50415408	LED downlight Premium Line black 9W 4000K IP44 dimmable	Ø117	22	IP44	Black (RAL 9005)	Yes	30000	9	220-240V AC	25	Ø110	520	4000K	>80	120°
 50415411	LED downlight Premium Line black 11W 4000K IP44 dimmable	Ø180	22	IP44	Black (RAL 9005)	Yes	30000	11	220-240V AC	25	Ø165	750	4000K	>80	120°
 50415415	LED downlight Premium Line black 15W 4000K IP44 dimmable	Ø240	22	IP44	Black (RAL 9005)	Yes	30000	15	220-240V AC	25	Ø225	1000	4000K	>80	120°

LED panel




50413550

LED panel

SKU	Product name	Diameter (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Input Voltage	Installation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
 50413550	LED panel recessed round 6W 3000K IP65 dimmable	Ø75	20	IP65	White	Yes	30000	6	220-240V AC	11	Ø55	420	3000K	>80	120°
 50413551	LED panel recessed round 8W 3000K IP65 dimmable	Ø100	20	IP65	White	Yes	30000	8	220-240V AC	11	Ø80	610	3000K	>80	120°
 50413552	LED panel recessed round 11W 3000K IP65 dimmable	Ø125	20	IP65	White	Yes	30000	11	220-240V AC	11	Ø105	900	3000K	>80	120°

Monza



50258810



Alba



50258811









Piatto





50258833








LED downlights 3W

SKU	Product name	Diameter (mm)	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Output amperage	Installation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
 50258803	LED downlight Monza round 3W 2700K aluminium IP65 dimmable tilttable	Ø60			20	IP65	Aluminium (brushed)	Yes	30000	3	700	20	Ø52	140	2700K	>80	40°
 50258810	LED downlight Monza round 3W 2700K white IP65 dimmable tilttable	Ø60			20	IP65	White (RAL 9003)	Yes	30000	3	700	20	Ø52	140	2700K	>80	40°
 50258811	LED downlight Monza round 3W 2700K black IP65 dimmable tilttable	Ø60			20	IP65	Black (RAL 9005)	Yes	30000	3	700	20	Ø52	140	2700K	>80	40°
 50258303	LED downlight Alba square 3W 2700K aluminium IP65 dimmable tilttable		60	60	20	IP65	Aluminium (brushed)	Yes	30000	3	700	20	Ø52	140	2700K	>80	40°
 50258310	LED downlight Alba square 3W 2700K white IP65 dimmable tilttable		60	60	20	IP65	White (RAL 9003)	Yes	30000	3	700	20	Ø52	140	2700K	>80	40°
 50258311	LED downlight Alba square 3W 2700K black IP65 dimmable tilttable		60	60	20	IP65	Black (RAL 9005)	Yes	30000	3	700	20	Ø52	140	2700K	>80	40°

SKU	Product name	Dia- meter (mm)	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimma- ble	Lifetime (hrs)	Wattage (W)	Output am- perage	Instal- lation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
 50258833	LED downlight Piatto round 3W 2700K aluminium IP65 dimmable	Ø42			50	IP65	Alumi- nium (brushed)	Yes	30000	3	700	50	Ø36	140	2700K	>80	40°
 50258840	LED downlight Piatto round 3W 2700K white IP65 dimmable	Ø42			50	IP65	White (RAL 9003)	Yes	30000	3	700	50	Ø36	140	2700K	>80	40°







LED downlights 5W







SKU	Product name	Dia- meter (mm)	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimma- ble	Lifetime (hrs)	Wattage (W)	Output am- perage	Instal- lation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
 50258845	LED downlight Montella round 5W 2700K aluminium IP65 dimmable tilttable	Ø90			40	IP65	Alumi- nium (brushed)	Yes	30000	5	350	40	Ø82	400	2700K	>80	40°
 50258705	LED downlight Montella round 5W 2700K white IP65 dimmable tilttable	Ø90			40	IP65	White (RAL 9003)	Yes	30000	5	350	40	Ø82	400	2700K	>80	40°
 50258706	LED downlight Montella round 5W 2700K black IP65 dimmable tilttable	Ø90			40	IP65	Black (RAL 9005)	Yes	30000	5	350	40	Ø82	400	2700K	>80	40°
 50258355	LED downlight Lecco square 5W 2700K aluminium IP65 dimmable tilttable		90	90	40	IP65	Alumi- nium (brushed)	Yes	30000	5	350	40	Ø82	400	2700K	>80	40°
 50258755	LED downlight Lecco square 5W 2700K white IP65 dimmable tilttable		90	90	40	IP65	White (RAL 9003)	Yes	30000	5	350	40	Ø82	400	2700K	>80	40°
 50258756	LED downlight Lecco square 5W 2700K black IP65 dimmable tilttable		90	90	40	IP65	Black (RAL 9005)	Yes	30000	5	350	40	Ø82	400	2700K	>80	40°



LED downlights 7W

SKU	Product name	Dia- meter (mm)	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimma- ble	Lifetime (hrs)	Wattage (W)	Output am- perage	Instal- lation height (mm)	Cut hole size (mm)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle
 50258907	LED downlight Argenta round 7W 2700K aluminium IP65 dimmable tilttable	Ø90			50	IP65	Alumi- nium (brushed)	Yes	30000	7	350	50	Ø82	650	2700K	>80	40°
 50259307	LED downlight Argenta round 7W 2700K white IP65 dimmable tilttable	Ø90			50	IP65	White (RAL 9003)	Yes	30000	7	350	50	Ø82	650	2700K	>80	40°
 50258917	LED downlight Cantello square 7W 2700K aluminium IP65 dimmable tilttable		90	90	50	IP65	Alumi- nium (brushed)	Yes	30000	7	350	50	Ø82	650	2700K	>80	40°
 50259317	LED downlight Cantello square 7W 2700K white IP65 dimmable tilttable		90	90	50	IP65	White (RAL 9003)	Yes	30000	7	350	50	Ø82	650	2700K	>80	40°



SKU	Product name	Diameter (mm)	Length (mm)	Width (mm)	Height (mm)	IP value	Dimmable	Input Voltage	Output amperage
 50349104	LED driver 700mA Max. 6W 4-9V		48	30	20	IP65	Yes	220-240V AC	700mA
 50349136	LED driver 700mA Max 13W 10-18V	55			25	IP65	Yes	220-240V AC	700mA
 50349108	LED driver 700mA Max. 29W 21-42V	64			30	IP65	Yes	220-240V AC	700mA
 50349171	LED driver 350mA Max. 10W 14-29V		58	35	20	IP65	Yes	220-240V AC	350mA
 50349172	LED driver 350mA Max. 15W 21-42V	56			25	IP65	Yes	220-240V AC	350mA
 50256502	Connectorbox double incl. 2m wire		40	26	14	IP20			





UPHIX® 50258811
3W 700mA 40D 3.2V IP65

©