




2 - LED PANELS






Functional lighting for workspaces, offices, (semi) public spaces such as health centres and schools. Yphix LED Panels are among the best in the market and come with a PMMA lightguide plate instead of the common plastic. This means they don't discolour and ensure the best quality light. They feature a patented solution to avoid seams and cracks which attract insects who enter the panel. The weldless corners are double welded on the in- and outside. The honeycomb-structured backplate makes the panel extra solid. They'll keep their good looks, year after year. And they come with multiple driver options.

YPHIX LED PANEL QUALITY FEATURES:

- PMMA lightguide plate that does not discolour
- Weldless corners, double welded on the in- and outside
- Multiple flicker-free driver options:
 - Non dimmable (Wieland or 2m connection cable)
 - 1-10V dimmable (Wieland or 2m connection cable)
 - Zigbee dimmable
 - Triac dimmable
 - Dali dimmable
- Excellent line meets the high standard of glare value URG<19
- Mounting frames and suspension sets (steel wire) available
- Available CCT: 3000K, 4000K and 6000K
- Guarantee LED panels: 5 years
- Guarantee LED Back-lit panels: 3 years




LED panel Pro

SKU	Product name	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle	URG
 50233000	LED panel Pro 60x60cm 40W 3000K	595	595	10	IP40	White (RAL 9003)	Yes	54000	40	4100	3000K	>80	120°	<22
 50233010	LED panel Pro 60x60cm 40W 4000K	595	595	10	IP40	White (RAL 9003)	Yes	54000	40	4100	4000K	>80	120°	<22
 50233020	LED panel Pro 60x60cm 40W 6000K	595	595	10	IP40	White (RAL 9003)	Yes	54000	40	4100	6000K	>80	120°	<22
 50233200	LED panel Pro 120x30cm 40W 3000K	1195	295	10	IP40	White (RAL 9003)	Yes	54000	40	4100	3000K	>80	120°	<22
 50233210	LED panel Pro 120x30cm 40W 4000K	1195	295	10	IP40	White (RAL 9003)	Yes	54000	40	4100	4000K	>80	120°	<22





LED panel Excellent

SKU	Product name	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle	URG
 50233050	LED panel Excellent 60x60cm 40W 3000K	595	595	10	IP40	White (RAL 9003)	Yes	54000	40	3000	3000K	>80	90°	<19
 50233060	LED panel Excellent 60x60cm 40W 4000K	595	595	10	IP40	White (RAL 9003)	Yes	54000	40	3000	4000K	>80	90°	<19
 50233250	LED panel Excellent 120x30cm 40W 3000K	1195	295	10	IP40	White (RAL 9003)	Yes	54000	40	3000	3000K	>80	90°	<19
 50233260	LED panel Excellent 120x30cm 40W 4000K	1195	295	10	IP40	White (RAL 9003)	Yes	54000	40	3000	4000K	>80	90°	<19



LED panel Back-lit

SKU	Product name	Length (mm)	Width (mm)	Height (mm)	IP value	Colour	Dimmable	Lifetime (hrs)	Wattage (W)	Lumen (Lm)	Kelvin value (K)	CRI	Beam angle	URG
 50233100	LED panel Back-lit 60x60cm 40W 3000K	595	595	40	IP20	White (RAL 9003)	No	54000	40	4100	3000K	>80	120°	<22
 50233110	LED panel Back-lit 60x60cm 40W 4000K	595	595	40	IP20	White (RAL 9003)	No	54000	40	4100	4000K	>80	120°	<22



SKU	Product name	Diameter (mm)	Length (mm)	Width (mm)	Height (mm)	Colour
50239400	Mounting frame LED panel 60x60cm		602	602	50	White (RAL 9003)
50239401	Mounting frame LED panel 120x30cm		1202	302	50	White (RAL 9003)
50239900	LED panel suspension set	Ø1	Max. 1200			Stainless Steel



SKU	Product name	Length (mm)	Width (mm)	Height (mm)	IP value	Dimmable	Input Voltage	Output amperage (mA)
50239020	LED driver flicker-free (15 cm wire Wieland connectable)	200	63	40	IP20	No	220-240V AC	1000
50239022	LED driver flicker-free (2m connection cable)	119	42	25	IP20	No	220-240V AC	1000
50239030	LED driver flicker-free 1-10V dimmable (15cm wire Wieland connectable)	103	48	39	IP20	Yes	220-240V AC	1050
50239032	LED driver flicker-free 1-10V dimmable (2m connection cable)	175	45	30	IP20	Yes	220-240V AC	1050
50239035	LED driver flicker-free TRIAC dimmable (2m connection cable)	208	45	34	IP20	Yes	220-240V AC	1000
50239040	LED driver flicker-free Dali system (15cm wire Dali connectable)	165	50	35	IP20	Yes	220-240V AC	1000
50208702	LED driver flicker-free Zigbee dimmable	210	50	33	IP20	Yes	220-240V AC	Variable (350-1000)

